



ArcelorMittal

Atak® Medium

Welded fence with Crapal®2 coating

Product description

Welded mesh in high tensile steel especially suitable for the protection of forestry

- Progressive meshes
- Horizontal wires in high tensile steel (70 to 90 kg/mm²)
- Product complies with EN 10223-4 standard

Applications

- Agriculture
- Forestry
- Industry
- Housing



Characteristics


Nomination	Height (cm)	Length (m)	Weight (kg)	Rolls/pallet
120-11-15	121.9	50	22.0	12
150-13-15	149.9	50	26.3	12
150-18-15	149.9	50	31.9	12
180-20-15	180.3	50	36.3	12
200-21-15	200.7	50	38.9	12

Mesh

- Top and bottom wires Ø 2.25 mm R 70 to 90 kg/mm²
- Horizontal wires Ø 1.90 mm R 70 to 90 kg/mm²
- Vertical wires Ø 1.90 mm R 40 to 55 kg/mm²

Atak® Medium

Dimensions



120-11-15

5 x 101.6 mm	2 x 127 mm	3 x 152.4 mm
1 219 mm		
152.4 mm		

150-13-15

5 x 101.6 mm	3 x 127 mm	4 x 152.4 mm
1 499 mm		
152.4 mm		

150-18-15

5 x 50.8 mm	5 x 76.2 mm	3 x 101.6 mm	2 x 127 mm	2 x 152.4 mm
1 499 mm				
152.4 mm				

180-20-15

5 x 50.8 mm	5 x 76.2 mm	3 x 101.6 mm	2 x 127 mm	4 x 152.4 mm
1 803 mm				
152.4 mm				

200-21-15

5 x 50.8 mm	5 x 76.2 mm	3 x 101.6 mm	2 x 127 mm	4 x 152.4 mm	2032 mm
2 007 mm					
152.4 mm					